



浩畅半导体
www.szhaochang.cn

2SK3019 SOT-23

N-Channel MOSFET



产
品
规
格
书

承
认
书

客户确认:				公司签章:
部门	工程部	品保部	采购部	
签名				
日期				

**SOT-23 Plastic-Encapsulate MOSFETS****2SK3019 N-Channel MOSFET****■ Features**

- Low on-resistance.
- Fast switching speed.
- Low voltage drive (2.5V) makes this device ideal for portable equipment.
- Easily designed drive circuits.
- Easy to parallel.

**■ Absolute Maximum Ratings Ta = 25°C**

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V _{DS}	30	V
Gate-Source Voltage	V _{G_S}	±20	
Continuous Drain Current	I _D	±100	mA
Continuous Drain Current Pulsed *1	I _{D_P}	±400	
Power Dissipation *2	P _D	150	mW
Junction Temperature	T _J	150	°C
Storage Temperature Range	T _{Stg}	-55 to 150	

*1 P_W≤10μs, Duty cycle≤1%

*2 With each pin mounted on the recommended lands.

■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	V _{DSS}	I _D =100μA, V _{G_S} =0V	30			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{D_S} =30V, V _{G_S} =0V			1	uA
Gate-Body Leakage Current	I _{GSS}	V _{D_S} =0V, V _{G_S} =±20V			±1	uA
Gate Threshold Voltage	V _{G_{S(th)}}	V _{D_S} =V _{G_S} , I _D =100 μA	0.8		1.5	V
Static Drain-Source On-Resistance	R _{D_{S(on)}}	V _{G_S} =4V, I _D =10mA		5	8	Ω
		V _{G_S} =2.5V, I _D =1mA		7	13	
Forward Transfer admittance	Y _{fs}	V _{D_S} =3V, I _D =10mA	20			mS
Input Capacitance	C _{iss}	V _{G_S} =0V, V _{D_S} =5V, f=1MHz		13		pF
Output Capacitance	C _{oss}			9		
Reverse Transfer Capacitance	C _{rss}			4		
Turn-On DelayTime	t _{d(on)}	V _{G_S} =5V, V _{D_S} =5V, R _L =500 Ω, R _{GEN} =10 Ω		15		ns
Turn-On Rise Time	t _r			35		
Turn-Off DelayTime	t _{d(off)}			80		
Turn-Off Fall Time	t _f			80		

■ Marking

Marking	KN
---------	----

2SK3019 N-Channel MOSFET

■ Typical Characteristics




Fig.1 Typical output characteristics




Fig.2 Typical transfer characteristics




Fig.3 Gate threshold voltage vs. channel temperature




Fig.4 Static drain-source on-state resistance vs. drain current (I)




Fig.5 Static drain-source on-state resistance vs. drain current (II)




Fig.6 Static drain-source on-state resistance vs. gate-source voltage




Fig.7 Static drain-source on-state resistance vs. channel temperature




Fig.8 Forward transfer admittance vs. drain current




Fig.9 Reverse drain current vs. source-drain voltage (I)

2SK3019 N-Channel MOSFET

■ Typical Characteristics




Fig.10 Reverse drain current vs.
source-drain voltage (II)




Fig.11 Typical capacitance vs.
drain-source voltage




Fig.12 Switching characteristics
(See Figures 13 and 14 for
the measurement circuit
and resultant waveforms)